

## Roulement conique 4388-4335-TIMKEN - 4388-4335-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/4388-4335-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings					Part Number		
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> Y	Dynamic <sup>(3)</sup> C <sub>2</sub>	Factor <sup>(4)</sup> K	Static C <sub>3</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
41.275	90.488	39.688	109000	2.70	2.11	51900	29300	20000	4388	4335
1.6250	3.5625	1.5625	44700			11600	5940	49000		

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>		
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max. Shaft Fillet Radius R <sup>(2)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max. Housing Fillet Radius r <sup>(3)</sup>	Backing Shoulder Dia. D <sub>s</sub>	Cage A <sub>1</sub> <sup>(4)</sup>	A <sub>2</sub> <sup>(5)</sup>						
40.386	33.338	-15.8	3.5	52.8	68.8	3.3	85.8	77.8	2.2	8.6	52.9	14.3	0.9872	5.24
1.5900	1.3125	-0.59	0.14	2.05	2.36	0.13	3.35	3.03	0.09	0.03				2.74

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952313238
Diam. intérieur	41.275 mm
Diam. intérieur	1 5/8" inch
Diam. extérieur	90.488 mm
Diam. extérieur	3 9/16" inch
Epaisseur	39.688 mm
Epaisseur	1 9/16" inch
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE