

## Roulement conique 541-532X-TIMKEN - 541-532X-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/541-532x-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Static <sup>(1)</sup> C <sub>0</sub>	Dynamic <sup>(2)</sup> C <sub>10</sub>	Static <sup>(2)</sup> C <sub>0</sub>	Factor <sup>(3)</sup> K	Inner	Outer	
mm	mm	mm	N	N	N	N				
41.275	107.950	36.512	17900	28700	4600	22700	1.57	541	532X	
1.6250	4.2500	1.4375			10000	5096				

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>		
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>1</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>1</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>	A <sub>3</sub> <sup>(1)</sup>				kg	
36.567	28.575	-12.2	3.5	53.8	58.8	3.3	188.8	94.8	2.7	1.8	94.3	16.1	0.0508	1.72
1.4350	1.1250	-0.48	0.14	2.01	2.33	0.13	3.94	3.70	0.10	0.04				3.80

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952313399
Diam. intérieur	41.275 mm
Diam. extérieur	107.95 mm
Épaisseur	36.512 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE