


## Roulement conique 39573-39521-TIMKEN - 39573-39521-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/39573-39521-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings					Part Number		
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>02</sub>	Factor <sup>(2)</sup> K	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
58.880	112.712	30.162	167000	2.36	42000	20700	1.12	224000	29273	29221
1.1875	4.4375	1.1875	37500		9300	5850		50300		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage				
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>1</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>1</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>	A <sub>3</sub> <sup>(1)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				kg	
30.162	23.812	-6.6	0.8	65.8	62.8	0.8	167.8	188.8	1.8	2.7	94.3	23.7	0.1074	1.81
1.1875	0.9375	-0.26	0.03	2.60	2.44	0.03	6.21	4.08	0.06	0.11				3.95

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952316420
Diam. intérieur	50.8 mm
Diam. extérieur	112.712 mm
Épaisseur	30.162 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE