


## Roulement conique 6465-6420-TIMKEN - 6465-6420-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/6465-6420-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> K	Dynamic <sup>(3)</sup> C <sub>90</sub>	Factor <sup>(4)</sup> K	Static C <sub>10</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
57.150	149.225	53.975	41100	1.30	10700	1.01	40300	6465	6420	
2.250	5.8750	2.1250	5260		2400		10400			

Bearing Dimensions										Geometry Factors			Bearing Weight		
Shaft					Housing					G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>			
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max. Shaft Fillet Radius R <sub>f</sub> <sup>(2)</sup>	Backling Shoulder Dia. d <sub>s</sub> <sup>(3)</sup>	Max. Housing Fillet Radius r <sup>(4)</sup>	Backling Shoulder Dia. D <sub>s</sub> <sup>(5)</sup>	Cage A <sub>1</sub> <sup>(6)</sup>	A <sub>2</sub> <sup>(7)</sup>							kg
54.225	44.400	-15.8	0.8	75.0	0.3	140.0	2.7	0.7				158.3	20.1	0.0021	5.07
2.1250	1.7500	-0.58	0.27	2.25	3.45	0.13	5.51	5.08	0.10	0.03					11.18

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952318226
Diam. intérieur	57.15 mm
Diam. extérieur	149.225 mm
Épaisseur	53.975 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE