


## Roulement conique 478-472X-TIMKEN - 478-472X-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/478-472x-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings					Part Number		
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>02</sub>	Factor <sup>(2)</sup> K	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
65.000	123.825	30.162	140000	2.30	32000	24000	1.52	190000	478	472X
2.5591	4.8750	1.1875	32200		8300	5500		425000		

Bearing Dimensions										Geometry Factors			Bearing Weight		
Shaft					Housing					Cage	G <sub>1</sub>	G <sub>2</sub>		C <sub>3</sub>	
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>	A <sub>3</sub> <sup>(1)</sup>				mm		mm
20.007	24.000	-4.1	2.3	73.0	77.0	3.3	115.0	100.0	1.5	2.2	77.3	23.0	0.1003	1.57	kg
1.1420	0.9447	-0.16	0.09	2.87	3.03	0.13	4.53	4.29	0.05	0.09				2.48	lb

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952319698
Diam. intérieur	65 mm
Diam. intérieur	2.559" inch
Diam. extérieur	123.825 mm
Diam. extérieur	4 7/8" inch
Epaisseur	30.162 mm
Epaisseur	1 3/16" inch
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE