

## Roulement conique 29590-29521-TIMKEN - 29590-29521-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/29590-29521-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number		
Bore d	O.D. D	Width T	Dynamic <sup>1)</sup> C <sub>1</sub>	Factor <sup>2)</sup> Y	Dynamic <sup>3)</sup> C <sub>2</sub>	Factor <sup>4)</sup> X	Static <sup>5)</sup> C <sub>0</sub>	Inner	Outer		
mm	mm	mm	N		N		N				
66.675	110.000	25.400	121000	1.40	1.21	33000	26000	1.27	167000	29590	29521
2.6250	4.3311	1.0000	29450			7810	5916		30300		

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Width		ER. Dr.		Shaft		Housing		Cage		G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>		
B	C	mm	μm	Max. Shaft Fillet Radius R <sub>1</sub>	Backling Shoulder Dia. d <sub>s</sub>	Max. Housing Fillet Radius r <sub>1</sub>	Backling Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>1)</sup>	A <sub>2</sub> <sup>1)</sup>				kg	
25.400	19.050	-0.8	3.5	73.0	86.8	1.3	104.8	99.0	2.1	1.4	70.3	25.9	0.1112	8.81
1.0000	0.7500	-0.03	0.14	2.87	3.15	0.05	4.09	3.90	0.08	0.06				2.01

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952319827
Diam. intérieur	66.675 mm
Diam. intérieur	2 5/8" inch
Diam. extérieur	110 mm
Diam. extérieur	4.331" inch
Epaisseur	25.4 mm
Epaisseur	1" inch
Poids	935 g
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE