


## Roulement conique 39589-39520-TIMKEN - 39589-39520-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/39589-39520-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number		
Bore d	O.D. D	Width T	Dynamic <sup>1)</sup> C <sub>1</sub>	Factor <sup>2)</sup> e	Dynamic <sup>3)</sup> C <sub>02</sub>	Factor <sup>3)</sup> K	Static C <sub>0</sub>	Inner	Outer		
mm	mm	mm	N		N		N				
66.675	112.712	30.162	167900	3.36	1.77	43000	20700	1.72	224000	29589	39520
1.1875	4.4375	1.1875	27500			9300	5000		50300		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage				
Width B	Width C	ER Dr. α <sup>1)</sup>	Max Shaft Fillet Radius R <sup>2)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>3)</sup>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>4)</sup>	A <sub>2</sub> <sup>5)</sup>	A <sub>3</sub> <sup>6)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>	kg	
30.162	23.812	-4.6	1.5	75.0	78.0	3.3	107.0	101.0	1.6	2.7	84.3	23.7	0.1024	1.17
1.1875	0.9375	-0.26	0.06	2.95	3.07	0.13	4.21	3.98	0.06	0.11			2.57	

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952319926
Diam. intérieur	66.675 mm
Diam. extérieur	112.712 mm
Épaisseur	30.162 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE