

## Roulement conique 6460-6420A-TIMKEN - 6460-6420A-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/6460-6420a-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number		
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> Y	Dynamic <sup>(3)</sup> C <sub>2</sub>	Factor <sup>(4)</sup> X	Static <sup>(5)</sup> C <sub>0</sub>	Inner	Outer		
mm	mm	mm	N		N		N				
73.025	149.225	53.975	411000	2.70	1.66	107000	46000	1.67	463000	6460	6420A
2.8750	5.8750	2.1250	52400			24000	14800		104000		

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft		Housing		Cage					G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>			
Width B	Width C	ER. Dr. e <sup>(1)</sup>	Max. Shaft Fillet Radius R <sup>(2)</sup>	Backing Shoulder Dia. d <sub>1</sub>	Max. Housing Fillet Radius r <sup>(3)</sup>	Backing Shoulder Dia. D <sub>1</sub>	A <sub>1</sub> <sup>(4)</sup>	A <sub>2</sub> <sup>(5)</sup>						
54.225	44.490	-15.8	3.5	87.8	55.8	0.8	148.8	131.8	2.7	8.7	158.3	20.1	0.0001	4.42
2.1250	1.7500	-0.59	0.14	3.43	3.99	0.03	5.91	5.16	0.10	0.03				9.75

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952321257
Diam. intérieur	73.025 mm
Diam. intérieur	2 7/8" inch
Diam. extérieur	149.225 mm
Diam. extérieur	5 7/8" inch
Epaisseur	53.975 mm
Epaisseur	2 1/8" inch
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE