


## Roulement conique 661-653-TIMKEN - 661-653-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/661-653-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number		
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Factor <sup>(3)</sup> f	Dynamic <sup>(1)</sup> C <sub>02</sub>	Factor <sup>(2)</sup> K	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N			N		N			
79.375	146.050	41.275	24700	2.41	1.47	6400	4600	1.42	33500	601	652
3.1250	5.7500	1.6265	15500			14400	10700		75300		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>		
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(2)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>(2)</sup>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>(3)</sup>	A <sub>2</sub> <sup>(3)</sup>	A <sub>3</sub> <sup>(3)</sup>				kg	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm			
41.275	91.750	-3.8	3.5	96.8	96.8	3.3	139.8	131.8	4.5	2.1	156.6	27.3	0.0919	2.88
1.6250	3.2500	-0.31	0.14	3.84	3.78	0.13	5.47	5.16	0.17	0.08				6.25

## CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952321974
Diam. intérieur	79.375 mm
Diam. extérieur	146.05 mm
Épaisseur	41.275 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE