


## Roulement conique

### H924043-H924010-TIMKEN - H924043-H924010-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/h924043-h924010-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>1)</sup> C <sub>1</sub>	Factor <sup>2)</sup> Y	Dynamic <sup>3)</sup> C <sub>2</sub>	Factor <sup>3)</sup> K	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
109.985	214.312	55.562	47900	2.97	12290	14900	81900	H924043	H924010	
4.3201	8.4375	2.1975	106000		27400	31900	133000			

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>		
Width B	Width C	ER. Dr. α <sup>4)</sup>	Max. Shaft Fillet Radius R <sup>5)</sup>	Backling Shoulder Dia. d <sub>s</sub>	Max. Housing Fillet Radius r <sup>6)</sup>	Backling Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>7)</sup>	A <sub>2</sub> <sup>7)</sup>	A <sub>3</sub> <sup>7)</sup>				kg	
52.388	55.688	6.5	3.5	131.2	135.8	3.3	255.8	186.0	6.6	3.6	245.6	32.2	0.1289	8.40
2.0625	1.5625	0.27	0.14	5.16	5.47	0.13	9.87	7.32	0.26	0.14				18.53

## CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952324494
Diam. intérieur	109.985 mm
Diam. extérieur	214.312 mm
Épaisseur	55.562 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE