

Roulement conique 74525-74853-TIMKEN - 74525-74853-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/74525-74853-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS

| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|---------|---------|--|----------------------------|--|----------------------------|--------------------------|-------|-------------|--|
| Bore d | O.D. D | Width T | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ K | Dynamic ⁽¹⁾ C ₂ | Factor ⁽²⁾ K | Static C ₀ | Inner | Outer | |
| mm | mm | mm | N | | N | | N | | | |
| 133.350 | 215.900 | 53.975 | 302500 | 1.10 | 123000 | 1.10 | 814000 | 3425 | 74853 | |
| 5.2500 | 8.5000 | 2.1260 | 15500 | | 22000 | | 138000 | | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|---------|--------------------------|---|--------------------------------------|---|--------------------------------------|--------------------------------------|-------------------------------|-------------------------------|------------------|----------------|----------------|-------------------------------|----------------|
| Shaft | | | | | Housing | | | | | Cage | G ₁ | G ₂ | | C ₃ |
| Width B | Width C | ER. Dr. α ⁽¹⁾ | Max. Shaft Fillet Radius R ⁽¹⁾ | Backing Shoulder Dia. d ₁ | Max. Housing Fillet Radius r ⁽¹⁾ | Backing Shoulder Dia. D ₁ | Backing Shoulder Dia. D ₂ | A ₁ ⁽¹⁾ | A ₂ ⁽¹⁾ | | | | A ₃ ⁽¹⁾ | |
| 53.975 | 47.625 | 2.3 | 0.5 | 146.0 | 152.0 | 3.3 | 209.0 | 196.0 | 4.8 | 2.8 | 362.9 | 66.5 | 0.1308 | 3.15 |
| 1.8750 | 1.8750 | 0.09 | 0.14 | 5.75 | 5.98 | 0.13 | 8.23 | 7.72 | 0.18 | 0.08 | | | | 15.77 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952325446 |
| Diam. intérieur | 133.35 mm |
| Diam. extérieur | 215.9 mm |
| Épaisseur | 53.975 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE