

Roulement conique M252330-M252310-TIMKEN - M252330-M252310-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/m252330-m252310-timken>

TAPERED ROLLER BEARINGS
SINGLE ROW • TYPE TS

TYPE TS



Bearing Dimensions				Load Ratings						Part Number	
Bore d	O.D. D	Width T		Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ Y	Dynamic ⁽³⁾ C ₀₂	Factor ⁽⁴⁾ K	Static C ₀		Inner	Outer
mm	mm	mm	N	N		N	N	N			
234.950	381.000	74.612	1200000	2.32	1.05	320000	195000	1.78	2670000	M252330	M252310
9.2500	15.0000	2.9375	205000			73200	41700		425000		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					G ₁	G ₂	C ₃		
Width B	Width C	ER. Dr. e ⁽¹⁾	Max Shaft Fillet Radius R ⁽²⁾	Backing Shoulder Dia. d _s	Max Housing Fillet Radius r ⁽³⁾	Backing Shoulder Dia. D _s	A ₁ ⁽⁴⁾	A ₂ ⁽⁵⁾						
74.612	57.950	-6.6	6.4	261.0	271.0	3.3	364.0	356.0	8.3	3.6	1050.2	226.1	0.1588	33.48
2.9375	2.2800	-0.26	0.25	10.28	10.67	0.13	14.32	14.02	0.32	0.14				73.80

CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952327877
Diam. intérieur	234.95 mm
Diam. intérieur	9 1/4" inch
Diam. extérieur	381 mm
Diam. extérieur	15" inch
Epaisseur	74.612 mm
Epaisseur	2 15/16" inch
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE