


## Roulement conique

### EE168400-168500-TIMKEN - EE168400-168500-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/ee168400-168500-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(3)</sup> C <sub>2</sub>	Factor <sup>(3)</sup> K	Static C <sub>2</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
1016.000	1270.000	101.600	290000	1.10	738000	1.18	863000	EE168400	168500	
41.3000	50.0000	4.0000	940000		1680000		1800000			

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage	G <sub>1</sub>	G <sub>2</sub>		C <sub>3</sub>
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max. Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max. Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>(2)</sup>	A <sub>2</sub> <sup>(2)</sup>	A <sub>3</sub> <sup>(2)</sup>				Ag	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	
101.600	66.675	127.8	9.7	1065.8	1070.0	9.7	1214.1	1219.8	21.8	-8.7	22588.3	3116.1	0.4018	266.85
4.0000	2.6250	5.00	0.38	41.54	42.12	0.38	47.80	47.84	0.80	-0.03				188.34

## CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952331652
Diam. intérieur	1016 mm
Diam. extérieur	1270 mm
Épaisseur	101.6 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE