

Roulement conique 665X-653-TIMKEN - 665X-653-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/665x-653-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS

Bearing Dimensions			Load Ratings						Part Number		
Bore d	O.D. D	Width T	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ Y	Dynamic ⁽³⁾ C ₂	Factor ⁽⁴⁾ X	Static C ₀	Inner	Outer		
mm	mm	mm	N		N		N				
85.000	146.050	41.275	247000	2.41	1.47	64000	46800	1.43	270000	850X	853
3.346	5.750	1.625	55500			14400	10700		75300		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft		Housing		Cage		Geometry Factors			kg					
Width B	Width C	ER. Dr. a ⁽¹⁾	Max. Shaft Fiber Radius R ₁	Backling Shoulder Dia. d ₁	d ₂	Max. Housing Fiber Radius r ₁	Backling Shoulder Dia. D ₁	D ₂		A ₁ ⁽²⁾	A ₂ ⁽³⁾	G ₁	G ₂	C ₃
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				
41.275	31.750	-2.8	3.5	95.8	101.6	3.3	128.8	131.8	4.5	2.1	126.6	27.3	0.0918	2.69
1.6250	1.2500	-0.31	0.14	3.74	3.98	0.13	5.47	5.18	0.17	0.08				5.83

CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952331942
Diam. intérieur	85 mm
Diam. intérieur	3.346" inch
Diam. extérieur	146.05 mm
Diam. extérieur	5 3/4" inch
Epaisseur	41.275 mm
Epaisseur	1 5/8" inch
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE