


## Roulement conique 6380-6320-B-TIMKEN - 6380-6320-B-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/6380-6320-b-timken>

**TAPERED ROLLER BEARINGS**  
**TYPE TSF**



| Bearing Dimensions |           |            |  | Load Ratings                |   |                             |                          |       |        | Part Number |  |
|--------------------|-----------|------------|--|-----------------------------|---|-----------------------------|--------------------------|-------|--------|-------------|--|
| Bore<br>d          | O.D.<br>D | Width<br>B | Dynamic <sup>(1)</sup><br>C <sub>1</sub> | Factors <sup>(1)</sup><br>e | Dynamic <sup>(2)</sup><br>C <sub>02</sub> | Factors <sup>(2)</sup><br>K | Static<br>C <sub>0</sub> | Inner | Outer  |             |  |
| mm                 | mm        | mm         | N  |                             | N   | N                           | N                        |       |        |             |  |
| 54.813             | 135.755   | 17.462     | 321800                                   | 0.32                        | 1.85                                      | 82000                       | 46200                    | 1.80  | 464000 | 6380        |  |
| 2.1580             | 5.3447    | 0.6875     | 72300                                    |                             | 18700                                     | 10400                       |                          |       | 90900  | 6320-B      |  |

| Bearing Dimensions |            |                             |  | Shaft                             |   | Housing                                    |  | Geometry Factors |                |                | Bearing Weight |      |
|--------------------|------------|-----------------------------|--|-----------------------------------|---|--|--|------------------|----------------|----------------|----------------|------|
| Width<br>B         | Width<br>C | Eff. Dia.<br>d <sub>1</sub> | Outer Ring<br>Ridge O.D.<br>D <sub>1</sub> | Flange<br>Width<br>C <sub>1</sub> | Max Shaft<br>File Radius<br>(R <sup>(1)</sup> ) | Sealing<br>Shoulder Dia.<br>d <sub>2</sub> | Sealing<br>Shoulder Dia.<br>D <sub>1</sub> | G <sub>1</sub>   | G <sub>2</sub> | C <sub>2</sub> | kg             |      |
| mm                 | mm         | mm                          | mm   | mm                                | mm  | mm   | mm   |                  |                |                | lbs.           |      |
| 56.007             | 44.468     | -15.3                       | 143.078                                    | 7.258                             | 0.2   | 70.6                                       | 71.9                                       | 128.8            | 123.5          | 22.4           | 0.9827         | 4.18 |
| 2.2050             | 1.7500     | -0.78                       | 5.6327                                     | 0.2725                            | 0.03  | 2.78                                       | 2.80                                       | 4.98             |                |                |                | 9.25 |

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | TIMKEN        |
| N° Ean13        | 3663952337845 |
| Diam. intérieur | 54.813 mm     |
| Diam. intérieur | 2.158" inch   |
| Diam. extérieur | 135.755 mm    |
| Diam. extérieur | 5.345" inch   |
| Epaisseur       | 56.007 mm     |
| Epaisseur       | 2.205" inch   |
| Conditionnement | 1             |

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE