

Roulement conique 635-632-B-TIMKEN - 635-632-B-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/635-632-b-timken>

TAPERED ROLLER BEARINGS
TYPE TSF

| Bearing Dimensions | | | Load Ratings | | | | | | | Part Number | |
|--------------------|----------|-------------|------------------------------|----------------------------|---------------------------------|----------------------------|--------------|-------|-------|-------------|-------|
| Bore ϕ | O.D. D | Width T_1 | Dynamic ⁽¹⁾ C_1 | Factors ⁽¹⁾ e | Dynamic ⁽²⁾ C_{10} | Factors ⁽²⁾ K | Static C_2 | Inner | Outer | | |
| mm | mm | mm | N | | N | N | N | | | | |
| 75 | 136.525 | 41.275 | 22000 | 0.36 | 1.88 | 89400 | 3700 | 1.81 | 29800 | 625 | 632-B |
| 2.280 | 5.3750 | 1.6200 | 524000 | | 13000 | 8420 | 67000 | | | | |

| Bearing Dimensions | | | Shaft | | | Housing | | Geometry Factors | | | Bearing Weight | |
|--------------------|-----------|------------------------|-----------------------------|--------------------|----------------------------------|-----------------------------|-----------------------------|-----------------------------|-------|-------|----------------|------|
| Width B | Width C | Eff. Dia. ϕ_{eff} | Outer Ring Ridge O.D. D_1 | Flange Width C_1 | Max Shaft Fillet Radius R_{fs} | Sealing Shoulder Dia. d_1 | Sealing Shoulder Dia. d_2 | Sealing Shoulder Dia. d_3 | G_1 | G_2 | C_{10} | kg |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | lbs. |
| 41.275 | 39.750 | -11.2 | 143.800 | 3.137 | 3.3 | 68.0 | 70.0 | 125.0 | 106.4 | 21.0 | 0.2804 | 3.16 |
| 1.6200 | 1.5500 | -0.44 | 5.6500 | 0.2410 | 0.14 | 2.72 | 2.75 | 4.92 | | | | 0.94 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952337944 |
| Diam. intérieur | 57.15 mm |
| Diam. extérieur | 136.525 mm |
| Épaisseur | 41.275 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE