

Roulement conique

H414249-H414210-B-TIMKEN - H414249-H414210-B-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/h414249-h414210-b-timken>

TAPERED ROLLER BEARINGS

TYPE TSF

| Bearing Dimensions | | | | | | | | | | Load Ratings | | | | | Part Number | |
|--------------------|-----------|------------|--|-----------------------------|---|-----------------------------|--------------------------|-------|-------|--------------|--|--|--|--|-------------|--|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factors ⁽¹⁾ e | Dynamic ⁽²⁾ C ₀₂ | Factors ⁽²⁾ K | Static C ₀ | Inner | Outer | | | | | | | |
| mm | mm | mm | N | | N | | N | | | | | | | | | |
| 71.437 | 136.525 | 41.275 | 32200 | 0.26 | 1.57 | 83700 | 51800 | 1.52 | 32500 | | | | | | | |
| 2.8125 | 5.3750 | 1.6250 | 72000 | | | 19800 | 11800 | | 75400 | | | | | | | |

| Bearing Dimensions | | | | | | | | | | Shaft | | | Housing | | | Geometry Factors | | | Bearing Weight |
|--------------------|------------|-----------------------------|--|-----------------------------------|--|--|--|--|--|-------|----------------|----------------|----------------|--|--|------------------|------|--|----------------|
| Width B | Width C | Eff. Dia. d ₁ | Outer Ring Ridge O.D. D ₁ | Flange Width C ₁ | Max Shaft File Radius R ⁽¹⁾ | Sealing Shoulder Dia. d ₂ | Sealing Shoulder Dia. d ₃ | Sealing Shoulder Dia. d ₄ | Sealing Shoulder Dia. d ₅ | | G ₁ | G ₂ | C ₀ | | | | kg | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | | | | | | | |
| 41.275 | 31.750 | -18.9 | 143.637 | 7.112 | 3.5 | 88.3 | 88.9 | 128.8 | | 112.8 | 22.9 | 0.3827 | | | | | 2.66 | | |
| 1.6250 | 1.2500 | -0.43 | 5.6950 | 0.2800 | 0.14 | 3.27 | 3.50 | 5.12 | | | | | | | | | 5.87 | | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952338750 |
| Diam. intérieur | 71.437 mm |
| Diam. intérieur | 2 13/16" inch |
| Diam. extérieur | 136.525 mm |
| Diam. extérieur | 5 3/8" inch |
| Epaisseur | 41.275 mm |
| Epaisseur | 1 5/8" inch |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE