


## Roulement à rotule sur bille 1214-K-TVH-C3-H214-FAG - 1214-K-TVH-C3-H214-FAG

<https://www.123roulement.com/roulement-palier/roulement-bille/rotules-bille/1214-k-tvh-c3-h214-fag>

**Self-aligning ball bearings 1214-K-TVH-C3 + H214**  
main dimensions to DIN 630 and DIN 5415, with tapered bore and adapter sleeve



$d_{int}$	60 mm
D	125 mm
B	24 mm
$B_{s,max}$	5 mm
c	14 mm
$D_1$	106.6 mm
$D_{s,max}$	116 mm
$D_{s1}$	92 mm
d	70 mm
$d_1$	87.7 mm
$d_{s,max}$	79 mm
$d_{s1,min}$	75 mm
l	41 mm
$r_{s,max}$	1.5 mm
	H214 Moss, adapter sleeve
m	1.23 kg Moss
$m_1$	0.63 kg Moss, adapter sleeve
C	35000 N Basic dynamic load rating, radial
e	0.19
$Y_1$	3.36
$Y_2$	5.21
$C_{10}$	13700 N Basic static load rating, radial
$Y_0$	3.52
$n_b$	6000 1/min Limiting speed
$n_g$	7900 1/min Reference speed
$C_{10}$	800 N Fatigue limit load, radial

### CARACTÉRISTIQUES PRODUIT

Marque	FAG
N° Ean13	3663952346250
Diam. intérieur	60 mm
Diam. extérieur	125 mm
Épaisseur	24 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE