

33015-TIMKEN - 33015-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/33015-timken>

TAPERED ROLLER BEARINGS

SINGLE-ROW • IsoClass

IsoClass

Bearing Dimensions				Load Ratings										Part Number		
Bore d	O.D. D	Width B		Dynami ⁽¹⁾ C ₁	Factor ⁽²⁾ e		Dynami ⁽¹⁾ C ₂	Factor ⁽²⁾ e ₂		Static C ₁₀				Assembly Inside/Outer		
mm	in	mm	in	N			N			N						
75.000	2.953	115.000	4.528	21.000	1.225		187000	4200	0.21	2.01		68000	24700	1.96	220000	53700
Bearing Dimensions																
				Shaft										Geometry Factors		
Width B	Width C	ER C ₁	ER C ₂	Max Shaft Fillet Radius r _{f1}	Backing Shoulder Dia. d _{s1}	Backing Shoulder Dia. d _{s2}	Max Housing Fillet Radius r _{f2}	Housing Backing Shoulder Dia. D _{s1}	Housing Backing Shoulder Dia. D _{s2}	Cage			G ₁	G ₂	C ₃	Bearing Weight kg
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				
31.800	25.500	-7.6	0.5	85.0	90.0	1.5	110.0	100.0	1.5	2.5	105.4	47.2	0.1122			1.54
1.2206	1.0039	-0.30	0.06	3.27	3.54	0.06	4.33	3.94	0.06	0.10						1.54

CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952353562
Diam. intérieur	75 mm
Diam. extérieur	115 mm
Epaisseur	31 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE