

Roulement conique

XUB-30216-YFA30216-TIMKEN - XUB-30216-YFA30216-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/xub-30216-yfa30216-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • IsoClass

IsoClass

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynami ⁽¹⁾ C ₁	Factor ⁽²⁾ Y	Dynami ⁽³⁾ C ₀	Factor ⁽³⁾ C _{0e}	Static C ₀	Assembly Inner/Outer		
mm	mm	mm	N		N	N	N			
80.000	141.000	30.250	10400	1.42	42400	30500	1300	XUB-30216/YFA30216		
3.1496	5.5512	1.1908	3680		9530	8660	42000			

Bearing Dimensions										Geometry Factors		Bearing Weight	
Shaft					Housing					C ₁	C ₂		
Width B	Width C	ER Dr. a ⁽⁴⁾	Max Shaft Fillet Radius R ⁽⁵⁾	Backing Shoulder Dia. d _s	Max Housing Fillet Radius r ⁽⁶⁾	Backing Shoulder Dia. D _s	Capo	A ₁ ⁽⁷⁾	A ₂ ⁽⁸⁾			G ₁	G ₂
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	
20.000	22.000	-0.0	0.5	80.0	2.0	130.0	130.0	3.0	3.0	80.7	28.4	0.0771	1.88
1.1024	0.8661	-0.08	0.02	3.14	0.08	5.24	5.24	0.15	0.14			0.0771	3.98

CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952353661
Diam. intérieur	80 mm
Diam. extérieur	141 mm
Épaisseur	30.25 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE