

## Roulement conique 30228-TIMKEN - 30228-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/30228-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • IsoClass

**IsoClass**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynami <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(1)</sup> Y	Dynami <sup>(2)</sup> C <sub>0</sub>	Factor <sup>(2)</sup> K	Static C <sub>0</sub>	Assembly Inner/Outer		
mm	mm	mm	N	N	N	N	N			
in	in	in	lbf	lbf	lbf	lbf	lbf			
140.000	250.000	45.750	302900	1.44	139000	98900	1.24	648000	30228	
5.5118	9.8425	1.8012	113000		25200	21800		146000		

  

Bearing Dimensions										Geometry Factors			Bearing Weight
Shaft					Housing					Cage			
Width B	Width C	ER Co. a <sup>(1)</sup>	Max Shift Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Backing Fillet Radius r <sup>(1)</sup>	Max Housing Shoulder Dia. D <sub>s</sub>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>2</sub>	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg
in	in	in	in	in	in	in	in	in	in	in	in	in	lbs
42.000	36.000	2.8	4.8	107.0	106.0	3.0	234.0	227.0	4.3	3.4			8.80
1.6535	1.4173	0.11	0.19	6.18	6.48	0.12	9.21	8.94	0.17	0.29			19.55

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952354033
Diam. intérieur	140 mm
Diam. extérieur	250 mm
Épaisseur	45.75 mm
Poids	8680 g
Conditionnement	1
Norme	Sans norme

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE