

## Roulement conique 350A-353D-TIMKEN - 350A-353D-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/350a-353d-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDO

**TYPE TDO**

Bearing Dimensions				Load Ratings							
Bore d	O.D. D	Width T	Double Outer Ring Width C	Dynamic <sup>(1)</sup> C <sub>10</sub>	Factor <sup>(2)</sup> Y <sub>1</sub>	Factor <sup>(2)</sup> Y <sub>2</sub>	Dynamic <sup>(3)</sup> C <sub>90</sub>	Factor <sup>(3)</sup> C <sub>90a</sub>	Dynamic <sup>(3)</sup> C <sub>500</sub>	Factor <sup>(3)</sup> K	
mm	mm	mm	mm	N			N	N	N		
40.000	90.119	50.800	44.450	106000	0.31	2.20	25100	13200	42000	1.51	
1.5748	3.5480	2.0000	1.7100	38500			9800	2900	9840		

  

Part Number		Shaft				Housing				Pin		Geometry Factors			Bearing Weight
Inner	Outer	Max. Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>1</sub>	Max. Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>1</sub>	K <sub>1</sub>	K <sub>2</sub>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>	C <sub>2</sub>			kg	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm			mm	
350A	353D	0.8	47.5	0.8	82.8	-	-	30.0	12.2	0.0792	1.53			3.38	
		0.03	1.87	0.03	3.23										

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952355719
Diam. intérieur	40 mm
Diam. extérieur	90.119 mm
Épaisseur	50.8 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE