

## Roulement conique 365A-363D-TIMKEN - 365A-363D-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/365a-363d-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDO

**TYPE TDO**

| Bearing Dimensions |        |         |                           | Load Ratings                           |                                      |                |                |  |  |       |  |
|--------------------|--------|---------|---------------------------|--|--------------------------------------|----------------|----------------|--|--|-------|--|
| Bore d             | O.D. D | Width T | Double Outer Ring Width C | Dynamic <sup>(1)</sup> C <sub>10</sub> | Factor <sup>(2)</sup> Y <sub>1</sub> | Y <sub>2</sub> | C <sub>0</sub> | Dynamic <sup>(1)</sup> C <sub>90</sub> | Factor <sup>(2)</sup> C <sub>200</sub> | K     |  |
| mm                 | mm     | mm      | mm                        | N                                      |                                      |                | N              | N                                      | N                                      |       |  |
| 41.275             | 90.000 | 50.010  | 42.010                    | 17700                                  | 0.32                                 | 2.11           | 3.14           | 26400                                  | 14400                                  | 40000 |  |
| 1.620              | 3.543  | 1.969   | 1.658                     | 3950                                   |                                      |                |                | 5930                                   | 3250                                   | 10300 |  |

  

| Part Number |       | Shaft                                   |                                      |   |                                      | Housing        |                |                |                | Pin            |                | Geometry Factors |  |      | Bearing Weight |
|-------------|-------|---|--------------------------------------|---|--------------------------------------|----------------|----------------|----------------|----------------|----------------|----------------|------------------|--|------|----------------|
| Inner       | Outer | Max. Shaft Fillet Radius R <sub>1</sub> | Backing Shoulder Dia. d <sub>1</sub> | Max. Housing Fillet Radius r <sub>1</sub> | Backing Shoulder Dia. D <sub>1</sub> | K <sub>1</sub> | K <sub>2</sub> | G <sub>1</sub> | G <sub>2</sub> | C <sub>1</sub> | C <sub>2</sub> |                  |  | kg   |                |
| mm          | mm    | mm                                      | mm                                   | mm  | mm                                   | mm             | mm             | mm             | mm             | mm             | mm             |                  |  | mm   |                |
| 365A        | 363D  | 3.5                                     | 55.0                                 | 0.8                                       | 84.0                                 | -              | -              | 33.8           | 14.0           | 0.0770         | 1.40           |                  |  | 2.11 |                |
|             |       | 0.14                                    | 2.17                                 | 0.05                                      | 3.31                                 |                |                |                |                |                |                |                  |  |      |                |

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | TIMKEN        |
| N° Ean13        | 3663952355726 |
| Diam. intérieur | 41.275 mm     |
| Diam. extérieur | 90 mm         |
| Épaisseur       | 50.01 mm      |
| Conditionnement | 1             |

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE