

Roulement conique 745A-742D-TIMKEN - 745A-742D-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/745a-742d-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDD

TYPE TDD

Bearing Dimensions				Load Ratings							
Bore d	O.D. D	Width T	Double Outer Ring Width C	Dynamic C ₁₀	Factor Y ₁	Factor Y ₂	C ₀	Dynamic C ₉₀	C ₅₀	Factor K	
mm	mm	mm	mm	N			N	N	N		
69.850	155.575	101.600	85.725	49600	0.33	2.08	3.08	87000	94400	170000	
2.750	6.1250	4.0000	3.3750	147000				21500	12200	38200	

Part Number		Shaft				Housing				Pin		Geometry Factors			Bearing Weight
Inner	Outer	Max. Shaft Fillet Radius R _{fs}	Backing Shoulder Dia. d _s	Max. Housing Fillet Radius r _h	Backing Shoulder Dia. D _s	K ₁	K ₂	G ₁	G ₂	C ₁	C ₂			kg	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				
745A	742D	3.5 0.14	86.0 3.40	1.5 0.06	142.0 5.63	-	-	155.0	26.3	0.0800		8.25	20.61		

CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952357690
Diam. intérieur	69.85 mm
Diam. extérieur	155.575 mm
Épaisseur	101.6 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE