

## Roulement conique

### DX641856-DX979640-TIMKEN - DX641856-DX979640-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/dx641856-dx979640-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDD

**TYPE TDD**

Bearing Dimensions				Load Ratings							
Bore d	O.D. D	Width T	Double Outer Ring Width C	Dynamic <sup>(1)</sup> C <sub>10</sub>	Factor <sup>(2)</sup> Y <sub>1</sub>	Factor <sup>(2)</sup> Y <sub>2</sub>	Dynamic <sup>(3)</sup> C <sub>90</sub>	Dynamic <sup>(3)</sup> C <sub>50</sub>	Dynamic <sup>(3)</sup> C <sub>100</sub>	Factor <sup>(4)</sup> K	
mm	mm	mm	mm	N			N	N	N		
203.200	317.500	146.050	111.125	157000	0.52	1.25	1.92	22300	20000	40000	1.12
9.930	12.500	5.700	4.370	33500				5200	4700	9300	

  

Part Number		Dimensions				Pin		Geometry Factors			Bearing Weight
Inner	Outer	Max. Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>1</sub>	Max. Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>1</sub>	K <sub>1</sub>	K <sub>2</sub>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg
DX641856	DX979640	4.3	221.8	1.5	296.5	22.23	19.21	92.5	126.1	0.1400	39.15
		0.17	8.94	0.06	11.75	0.89	0.41				86.33

## CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952360669
Diam. intérieur	203.2 mm
Diam. extérieur	317.5 mm
Épaisseur	146.05 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE