

## Roulement conique

### M241549-M241510CD-TIMKEN - M241549-M241510CD-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/m241549-m241510cd-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDO

**TYPE TDO**

Bearing Dimensions				Load Ratings							
Bore d	O.D. D	Width T	Double Outer Ring Width C	Dynamic <sup>(1)</sup> C <sub>10</sub>	Factor <sup>(2)</sup> Y <sub>1</sub>	Factor <sup>(2)</sup> Y <sub>2</sub>	Factor <sup>(2)</sup> Y <sub>3</sub>	Dynamic <sup>(1)</sup> C <sub>90</sub>	Dynamic <sup>(1)</sup> C <sub>50</sub>	Factor <sup>(2)</sup> K	
mm	mm	mm	mm	N	N	N	N	N	N	N	
204.788	292.100	125.415	101.600	198000	0.33	2.03	3.02	158000	86000	1.39	
8.9023	11.5000	4.9378	4.0000	2.9500				30000	16000		

  

Part Number		Dimensions				Pin		Geometry Factors			Bearing Weight
Inner	Outer	Max. Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>1</sub>	Max. Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>1</sub>	K <sub>1</sub>	K <sub>2</sub>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg
M241549	M241510CD	3.5	223.8	1.5	279.8	19.85	8.73	94.1	127.8	0.1279	24.66
		0.14	8.79	0.06	10.98	0.75	0.34				54.35

## CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952360690
Diam. intérieur	204.788 mm
Diam. extérieur	292.1 mm
Epaisseur	125.415 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE