


Douille à aiguilles YB2016-IKO - YB2016-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/douille/yb2016-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard			Mass (Ref.) g			Grease retained g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end		
31.750 (1 1/4)	—	—	—	—	—	—	—	—	—	—	YB 2016 57
Boundary dimensions mm(inch)		Standard mounting dimensions mm		Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring				
F_w	D	C	t_1	Shaft dia. mm Max. Min.	Housing bore dia. mm Max. Min.	C	C_0	rpm			
31.750 1 1/4	38.100 1 1/2	25.40 1.000	—	31.750 31.734 38.114 38.089	—	40 900	100 000	4 500	IRB 1616		

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952362359
Diam. intérieur	31.75 mm
Diam. extérieur	38.1 mm
Épaisseur	25.4 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE