

Roulement conique

EE291201-291753CD-TIMKEN - EE291201-291753CD-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/ee291201-291753cd-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDO

TYPE TDO

| Bearing Dimensions | | | | Load Ratings | | | | | | | |
|--------------------|---------|---------|---------------------------|--|--------------------------------------|--------------------------------------|--|--|--|-------------------------|--|
| Bore d | O.D. D | Width T | Double Outer Ring Width C | Dynamic ⁽¹⁾ C ₁₀ | Factor ⁽²⁾ Y ₁ | Factor ⁽²⁾ Y ₂ | Dynamic ⁽³⁾ C ₉₀ | Factor ⁽³⁾ C _{90a} | Dynamic ⁽³⁾ C ₅₀ | Factor ⁽³⁾ K | |
| mm | mm | mm | mm | N | | | N | N | N | | |
| 304.800 | 444.500 | 223.825 | 176.200 | 198000 | 0.38 | 1.78 | 23000 | 140000 | 40000 | 1.55 | |
| 12.000 | 17.500 | 8.8125 | 6.9250 | 24700 | | | 51700 | 33400 | 9000 | | |

| Part Number | | Dimensions | | | | Pin | | Geometry Factors | | | Bearing Weight |
|-------------|----------|---|--------------------------------------|---|--------------------------------------|----------------|----------------|------------------|----------------|----------------|----------------|
| Inner | Outer | Max. Shaft Fillet Radius R ₁ | Backing Shoulder Dia. d ₁ | Max. Housing Fillet Radius r ₁ | Backing Shoulder Dia. D ₁ | K ₁ | K ₂ | G ₁ | G ₂ | C ₁ | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | kg |
| EE291201 | 291753CD | 8.8 | 227.8 | 1.5 | 414.8 | 22.23 | 11.81 | 1579.2 | 244.8 | 0.1587 | 52.94 |
| | | 0.31 | 13.27 | 0.06 | 18.30 | 0.88 | 0.47 | | | | 254.98 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952362854 |
| Diam. intérieur | 304.8 mm |
| Diam. extérieur | 444.5 mm |
| Épaisseur | 223.825 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE