

Roulement conique

EE291250-291751CD-TIMKEN - EE291250-291751CD-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/ee291250-291751cd-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDO

TYPE TDO

| Bearing Dimensions | | | | Load Ratings | | | | | | | |
|--------------------|----------|----------|---------------------------|--|--------------------------------------|----------------|----------------|--|-------------------------|-----------------|------------------|
| Bore d | O.D. D | Width T | Double Outer Ring Width C | Dynamic ⁽¹⁾ C ₁₀ | Factor ⁽²⁾ Y ₁ | Y ₂ | C ₀ | Dynamic ⁽¹⁾ C ₉₀ | Factor ⁽²⁾ K | C ₅₀ | C ₁₀₀ |
| mm | mm | mm | mm | N | | | N | N | | N | N |
| 317.5000 | 444.5000 | 146.0500 | 98.4250 | 150000 | 0.38 | 1.78 | 2.68 | 220000 | 140000 | 400000 | 1.55 |
| 12.5000 | 17.5000 | 5.7000 | 3.8750 | 247000 | | | | 51700 | 33400 | 90000 | |

| Part Number | | Dimensions | | | | Pin | | Geometry Factors | | | Bearing Weight | |
|-------------|----------|---|--------------------------------------|---|--------------------------------------|----------------|----------------|------------------|----------------|----------------|----------------|--------|
| Inner | Outer | Max. Shaft Fillet Radius R ₁ | Backing Shoulder Dia. d ₁ | Max. Housing Fillet Radius r ₁ | Backing Shoulder Dia. D ₁ | K ₁ | K ₂ | G ₁ | G ₂ | C ₁ | C ₂ | kg |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm |
| EE291250 | 291751CD | 8.08 | 246.08 | 1.50 | 413.80 | 22.23 | 11.81 | 1579.2 | 244.8 | 0.1557 | 95.32 | 121.76 |
| | | 0.31 | 13.82 | 0.08 | 18.30 | 0.88 | 0.47 | | | | | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952363561 |
| Diam. intérieur | 317.5 mm |
| Diam. extérieur | 444.5 mm |
| Épaisseur | 146.05 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE