

Roulement conique

HM261049H-HM261010CD-TIMKEN - HM261049H-HM261010CD-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/hm261049h-hm261010cd-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDO

TYPE TDO

| Bearing Dimensions | | | | Load Ratings | | | | | | | | | | |
|--------------------|---------|---------|---------------------------|------------------------|--------|-----------------------|----------------|------------------------|--------|-----------------------|--------|------------------------|--------|-----------------------|
| Bore d | O.D. D | Width T | Double Outer Ring Width C | Dynamic ⁽¹⁾ | | Factor ⁽²⁾ | | Dynamic ⁽¹⁾ | | Factor ⁽²⁾ | | Dynamic ⁽¹⁾ | | Factor ⁽²⁾ |
| mm | mm | mm | mm | C ₁₀ | N | Y ₁ | Y ₂ | C ₁₀ | N | C ₁₀ | N | C ₁₀ | N | K |
| 333.375 | 469.900 | 195.500 | 192.400 | 294000 | 131200 | 0.33 | 2.02 | 3.00 | 438000 | 201000 | 763000 | 367000 | 171000 | 1.34 |

| Part Number | | Dimensions | | | | Pin | | Geometry Factors | | | Bearing Weight |
|-------------|------------|---|--------------------------------------|---|--------------------------------------|----------------|----------------|------------------|----------------|----------------|----------------|
| Inner | Outer | Max. Shaft Fillet Radius R ₁ | Backing Shoulder Dia. d ₁ | Max. Housing Fillet Radius r ₁ | Backing Shoulder Dia. D ₁ | K ₁ | K ₂ | G ₁ | G ₂ | C ₁ | |
| HM261049H | HM261010CD | 6.4 | 303.8 | 1.5 | 449.5 | 28.58 | 15.81 | 3045.1 | 295.8 | 0.1880 | 85.90 |
| | | 0.25 | 14.25 | 0.35 | 17.70 | 1.13 | 0.47 | | | | 211.44 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952363707 |
| Diam. intérieur | 333.375 mm |
| Diam. extérieur | 469.9 mm |
| Épaisseur | 190.5 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE