

Roulement conique

LM772748-LM772710CD-TIMKEN - LM772748-LM772710CD-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/lm772748-lm772710cd-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDD

TYPE TDD

| Bearing Dimensions | | | | Load Ratings | | | | | | | |
|--------------------|---------|---------|---------------------------|------------------------|------|-----------------------|----------------|------------------------|-----------------|-----------------------|------|
| Bore d | O.D. D | Width T | Double Outer Ring Width C | Dynamic ⁽¹⁾ | | Factor ⁽²⁾ | | Dynamic ⁽¹⁾ | | Factor ⁽²⁾ | |
| mm | mm | mm | mm | C ₁₀ | C | Y ₁ | Y ₂ | C ₁₀ | C ₉₀ | C ₅₀ | K |
| in | in | in | in | lb | mm | | | lbf | klb | klb | |
| 488.950 | 634.873 | 180.975 | 136.525 | 324000 | 0.47 | 1.43 | 2.12 | 462000 | 300000 | 940000 | 1.24 |
| 19.250 | 24.990 | 7.125 | 5.375 | 72900 | | | | 105000 | 67000 | 189000 | |

| Part Number | | Dimensions | | | | Pin | | Geometry Factors | | | Bearing Weight |
|-------------|------------|---|--------------------------------------|---|--------------------------------------|----------------|----------------|------------------|----------------|----------------|----------------|
| Inner | Outer | Max. Shaft Fillet Radius R ₁ | Backing Shoulder Dia. d ₁ | Max. Housing Fillet Radius r ₁ | Backing Shoulder Dia. D ₁ | K ₁ | K ₂ | G ₁ | G ₂ | C ₁ | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | kg |
| LM772748 | LM772710CD | 6.4 | 92.8 | 1.5 | 69.5 | 28.98 | 14.36 | 947.5 | 622.2 | 0.2525 | 134.98 |
| | | 0.25 | 36.55 | 0.06 | 24.15 | 1.13 | 0.56 | | | | 298.54 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952366432 |
| Diam. intérieur | 488.95 mm |
| Diam. extérieur | 634.873 mm |
| Épaisseur | 180.975 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE