

## Roulement conique

### M281635-M281610CD-TIMKEN - M281635-M281610CD-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/m281635-m281610cd-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDD

**TYPE TDD**

Bearing Dimensions				Load Ratings							
Bore d	O.D. D	Width T	Double Outer Ring Width C	Dynamic <sup>(1)</sup> C <sub>10</sub>	Factor <sup>(2)</sup> Y <sub>1</sub>	Y <sub>2</sub>	Y <sub>3</sub>	C <sub>0</sub>	Dynamic <sup>(1)</sup> C <sub>90</sub>	C <sub>50</sub>	Factor <sup>(2)</sup> K
mm	mm	mm	mm	N				N	N	N	
635.000	933.450	377.825	301.625	10200000	0.33	2.03	3.02	1520000	865000	2620000	1.26
25.000	36.700	14.8750	11.8750	2395000				342000	195000	595000	

  

Part Number		Dimensions				Pin		Geometry Factors			Bearing Weight	
Inner	Outer	Max. Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>1</sub>	Max. Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>1</sub>	K <sub>1</sub>	K <sub>2</sub>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>	C <sub>2</sub>	kg
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
M281635	M281610CD	12.8	898.8	1.5	898.8	38.10	21.43	17204.9	775.6	0.3325		865.96
		0.47	27.52	0.06	25.04	1.50	0.84					1905.13

## CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952366883
Diam. intérieur	635 mm
Diam. extérieur	933.45 mm
Epaisseur	377.825 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE