


## Roulement à aiguilles TRI325230-IKO - TRI325230-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/tri325230-iko>



Shaft dia. mm	Identification number						Mass (Ref.) g	
	NA 49	NA 69	NA 48	TAFI	TRI	GTRI	g	d
32	—	—	—	—	TRI 325230	—	245	32

Boundary dimensions mm					Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring	
D	C	B	r <sub>s</sub> min <sup>(1)</sup>	r <sub>w</sub> S <sup>(2)</sup>	Min.	d <sub>s</sub> Max.	D <sub>s</sub> Max.	N	N	rpm	LRT 323630	
52	30	30.5	0.6	38	0.5	36	37	48	50 600	81 100	11 000	

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952371832
Diam. intérieur	32 mm
Diam. extérieur	52 mm
Épaisseur	30 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE