


Roulement à aiguilles NA4840-IKO - NA4840-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/na4840-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Inner Ring



| Shaft dia. mm | Identification number | | | | | | Mass (Ref.) | | | | | | |
|------------------------|-----------------------|---------------------------------|-----------------------------------|---------------------------------|---|---|----------------------|-----|---------|---------|-------|----------|----------|
| | NA 49 | NA 69 | NA 48 | TAFI | TRI | GTRI | g | d | | | | | |
| 200 | — | — | NA 4840 | — | — | — | 6 040 | 200 | | | | | |
| Boundary dimensions mm | | Standard mounting dimensions mm | | Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed ⁽¹⁾ | Assembled inner ring | | | | | | |
| D | C | B | r _s min ⁽²⁾ | r _w S ⁽³⁾ | Min. d _s | Max. d _s | Max. D _s | N | N | rpm | LRT | 20022050 | |
| 250 | 50 | — | 1.5 | 220 | 1.5 | 208 | 218 | 242 | 255 000 | 766 000 | 1 600 | LRT | 20022050 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952373171 |
| Diam. intérieur | 200 mm |
| Diam. intérieur | 7.874" inch |
| Diam. extérieur | 250 mm |
| Diam. extérieur | 9.843" inch |
| Epaisseur | 50 mm |
| Epaisseur | 1.969" inch |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE