

Roulement conique NP868174-329172-TIMKEN - NP868174-329172-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/np868174-329172-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDIT

TYPE TDIT

| Bearing Dimensions | | | | Load Ratings | | | | | | | | | | | |
|--------------------|-------|--------------------|-------------------|---------------------------|-------------------------|------|-------------------------------------|----------------|----------------|-------------------------|----------------|--------------------------------------|-------------------------|----|------------------------|
| Bore d | Taper | O.D. D | Width T | Double Inner Ring Width B | Dynamic C ₁₀ | e | Factor ¹⁾ Y ₁ | Y ₂ | C ₀ | Dynamic C ₉₀ | N | Factor ²⁾ C ₀₀ | Dynamic C ₅₀ | N | Factor ³⁾ K |
| mm | | mm | mm | mm | N | | | | | N | mm | | N | mm | |
| 304.655 11.9943 | 1:12 | 438.048 17.2460 | 131.762 5.1875 | 331.762 13.0615 | 180000 42000 | 0.33 | 2.04 | 2.03 | 28000 6200 | 15000 3000 | 48700 11000 | | 1.76 | | |

| Part Number | | Dimensions | | | Geometry Factors | | | Bearing Weight |
|-------------|--------|-------------------------|---------------------------|--------------------------------------|------------------|----------------|----------------|-----------------|
| Inner | Outer | Max Shaft Fillet Radius | Max Housing Fillet Radius | Backing Shoulder Dia. D _s | G ₁ | G ₂ | C ₃ | |
| | | mm | mm | mm | | | | kg (lb) |
| NP868174 | 329172 | 7.6 0.30 | 3.3 0.13 | 48.8 1.91 | 2051.2 | 257.0 | 0.1038 | 65.26 144.13 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952373461 |
| Diam. intérieur | 304.655 mm |
| Diam. extérieur | 438.048 mm |
| Épaisseur | 131.762 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE