

Roulement conique NA87700-87112D-TIMKEN - NA87700-87112D-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/na87700-87112d-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TNA

TYPE TNA

| Bearing Dimensions | | | | Load Ratings | | | | | | | | | |
|--------------------|---------|---------|---------------------------|--|------|--------------------------------------|----------------|--|-----------------|------------------|------------------|-------------------------|--|
| Bore d | O.D. D | Width T | Double Outer Ring Width C | Dynamic ⁽¹⁾ C ₁₀ | e | Factor ⁽²⁾ Y ₁ | Y ₂ | Dynamic ⁽³⁾ C ₉₀ | C ₅₀ | C ₁₀₀ | C ₂₀₀ | Factor ⁽⁴⁾ K | |
| mm | mm | mm | mm | N | | | | N | N | N | N | | |
| 177.800 | 282.575 | 107.950 | 71.325 | 798000 | 0.42 | 1.02 | 2.42 | 132000 | 62900 | 230000 | 230000 | 1.81 | |
| 7.000 | 11.1250 | 4.2500 | 3.1250 | 185000 | | | | 25700 | 21100 | 51700 | 51700 | | |

| Part Number | | Shaft | | | | Housing | | | | Pin | Bearing Weight |
|-------------|--------|--|--------------------------------------|--|--------------------------------------|----------------|----------------|-------|--|-----|----------------|
| Inner | Outer | Max Shaft Fillet Radius R ⁽¹⁾ | Backing Shoulder Dia. d _s | Max Housing Fillet Radius r ⁽²⁾ | Backing Shoulder Dia. D _s | K ₁ | K ₂ | | | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | | | |
| NA87700 | 87112D | 3.5 | 200.0 | 1.6 | 207.0 | - | - | 23.00 | | | |
| | | 0.14 | 7.87 | 0.08 | 10.50 | - | - | 50.80 | | | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952374321 |
| Diam. intérieur | 177.8 mm |
| Diam. extérieur | 282.575 mm |
| Épaisseur | 107.95 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE