

Roulement à aiguilles BRI203316-IKO - BRI203316-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/bri203316-iko>

MACHINED TYPE NEEDLE ROLLER BEARINGS
With Inner Ring, Inch Series

| Shaft dia. mm (inch) | Identification number | Mass (Ref.) g | Boundary dimensions mm(inch) | | | | | |
|------------------------------------|--------------------------|---|---|-------------------------------------|----------------------|--------|----------------|-----------------------|
| | | | d | D | C | B | F _w | (¹) S |
| 31.750 (1¼) | BRI 203316 | 220 | 31.750 (1¼) | 52.388 (2¼) | 25.400 (1) | 25.650 | 38.100 (1½) | 0.5 |
| Standard mounting dimensions mm | | Ball cyclic load rating C ₁₀ | Basic static load rating C ₀ | Allowable rotational speed(2) | Assembled inner ring | | | |
| d _s Min. | d _s Max. | | | | r _{al,max} | N | N | rpm |
| 37 | 37.1 | 45.1 | 1.5 | 43 700 | 66 900 | 11 000 | | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952375281 |
| Diam. intérieur | 31.75 mm |
| Diam. extérieur | 52.388 mm |
| Épaisseur | 25.65 mm |
| Poids | 485 g |
| Conditionnement | - |
| Norme | Sans norme |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE