


Roulement à aiguilles GBRI142616-IKO - GBRI142616-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/gbri142616-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F_w
22.225 ($\frac{9}{16}$)	GBRI 142616	167	22.225 ($\frac{9}{16}$)	41.275 ($\frac{1.625}{4}$)	25.400 ($\frac{1}{2}$)	25.650	28.575 ($\frac{1.125}{2}$)
Standard mounting dimensions mm		Sub-dynamic load rating C_1 N	Basic static load rating C_0 N	Allowable rotational speed (1) rpm	Assembled inner ring		
d_a Min.	d_a Max.				$r_{as\ max}$ (2)	C_1 N	C_0 N
27	27.5	36.3	0.6	43 900	75 300	5 500	LRBZ 141816

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377438
Diam. intérieur	22.225 mm
Diam. extérieur	41.275 mm
Épaisseur	25.65 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE