


Roulement à aiguilles GBRI162816-IKO - GBRI162816-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/gbri162816-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F_w
25.400 (1)	GBRI 162816	184	25.400 (1)	44.450 (1)	25.400 (1)	25.650	31.750 (1)

Standard mounting dimensions mm		Ball/needle lead ring C	Basic static load rating C_0	Allowable rotational speed (F) rpm	Assembled inner ring LRBZ 162016		
d_a	D_a						
Min.	Max.	$r_{a \text{ max}}$	N	N			
30.5	30.7	39.6	0.6	46 600	83 900	4 500	

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377445
Diam. intérieur	25.4 mm
Diam. extérieur	44.45 mm
Épaisseur	25.65 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE