


Roulement à aiguilles GBRI203316-IKO - GBRI203316-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/gbri203316-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F_w
31.750 (1 1/4)	GBRI 203316	235	31.750 (1/2)	52.388 (2/3)	25.400 (1)	25.650	38.100 (1 1/2)
Standard mounting dimensions mm		Ball/needle lead angle C	Basic static load rating C_0	Allowable rotational speed (1) C_1	Assembled inner ring		
Min.	Max.				Min.	Max.	rpm
37	37.1	47.3	0.6°	54 200	97 700	4 000	LRBZ 202416

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377469
Diam. intérieur	31.75 mm
Diam. extérieur	52.388 mm
Épaisseur	25.65 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE