


Roulement à aiguilles GBRI223516-IKO - GBRI223516-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/gbri223516-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
34.925 (1 3/8)	GBRI 223516	255	34.925 (1 3/8)	55.562 (2 1/8)	25.400 (1)	25.650	41.275 (1 5/8)

Standard mounting dimensions mm		Static load rating C ₀	Basic load rating C ₀	Allowable rotational speed (1)	Assembled inner ring		
d _a	D _a	r _{as} (2)	N	N			
Min.	Max.	Max.		rpm			
40.2	40.2	50.5	0.5	56 600	105 000	3 500	LRBZ 222616

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377483
Diam. intérieur	34.925 mm
Diam. intérieur	1 3/8" inch
Diam. extérieur	55.562 mm
Diam. extérieur	2 3/16" inch
Epaisseur	25.65 mm
Epaisseur	1.01" inch
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE