


## Roulement à aiguilles GBRI223516-IKO - GBRI223516-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/gbri223516-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F <sub>w</sub>
<b>34.925</b> (1 3/8)	<b>GBRI 223516</b>	255	34.925 (1 3/8)	55.562 (2 1/8)	25.400 (1)	25.650	41.275 (1 5/8)
Standard mounting dimensions mm		Sub-dynamic load rating C <sub>10</sub> N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed (1) rpm	Assembled inner ring		
d <sub>a</sub> Min.	d <sub>a</sub> Max.				D <sub>a</sub> Max.	r <sub>a</sub> mm	C <sub>1</sub> N
40.2	40.2	50.5	0.5	56 600	105 000	3 500	<b>LRBZ 222616</b>

Notes: (1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-packed. Perform proper lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377483
Diam. intérieur	34.925 mm
Diam. extérieur	55.562 mm
Épaisseur	25.65 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE