


## Roulement à aiguilles GBRI223520-IKO - GBRI223520-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/gbri223520-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			$d$	$D$	$C$	$B$	$F_w$
<b>34.925</b> (1 1/8)	<b>GBRI 223520</b>	316	34.925 $\pm$ 0.015	55.562 $\pm$ 0.025	31.750 $\pm$ 0.025	32.000	41.275 $\pm$ 0.025

Standard mounting dimensions mm		Sub-dynamic load rating $C_1$ N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring <b>LRBZ 222620</b>		
$d_a$ Min.	$d_a$ Max.						
40.2	40.2	50.5	0.5	67 000	130 000	3 500	

Notes: <sup>(\*)</sup> Maximum permissible corner radius of the housing.  
<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 2. The outer ring has an oil groove and an oil hole.  
3. No grease is pre-applied. Perform proper lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377490
Diam. intérieur	34.925 mm
Diam. extérieur	55.562 mm
Épaisseur	32 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE