


Roulement à aiguilles GBRI264116-IKO - GBRI264116-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/gbri264116-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
41.275 (1 5/8)	GBRI 264116	350	41.275 (1 5/8)	65.088 (2 5/8)	25.400 (1)	25.650	50.800 (2)
Standard mounting dimensions mm		Sub-dynamic load rating C ₁₀ N	Basic static load rating C ₀ N	Allowable rotational speed (1) rpm	Assembled inner ring		
d _a Min.	d _a Max.				r _{as} mm	1	
48	49	59.2	1	63 100	130 000	3 000	LRBZ 263216

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377537
Diam. intérieur	41.275 mm
Diam. extérieur	65.088 mm
Épaisseur	25.65 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE