

## Roulement à aiguilles GBR162412-IKO - GBR162412-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/gbr162412-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm <sup>(1)</sup>	
			$F$	$D$	$C$	$D_s$ Max.	$r_{as\ max}$
<b>25.400</b> (1)	<b>GBR 162412</b>	79	25.400 <sup>(1)</sup>	38.100 <sup>(1)</sup>	19.050 <sup>(2)</sup>	33.3	0.6
Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(3)</sup> rpm					
31 000	46 100	6 000					

Notes:<sup>(1)</sup> Maximum permissible corner radius of the housing.  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks:  
2. The outer ring has an oil groove and an oil hole.  
3. No grease is pre-packed. Perform proper lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377735
Diam. intérieur	25.4 mm
Diam. extérieur	38.1 mm
Épaisseur	19.05 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE