

## Roulement à aiguilles GBRI446828-IKO - GBRI446828-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/gbri446828-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F <sub>w</sub>
<b>69.850</b> (2 3/4)	<b>GBRI 446828</b>	<b>1 630</b>	<b>69.850</b> 2 3/4	<b>107.950</b> 4 1/4	<b>44.450</b> 1 3/4	<b>44.700</b>	<b>82.550</b> 3 1/4

  

Standard mounting dimensions mm		Sub-dynamic load rating C <sub>10</sub> N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed (1) rpm	Assembled inner ring		
d <sub>a</sub> Min.	d <sub>a</sub> Max.						
77	79	99.9	1.5	193 000	396 000	1 800	<b>LRBZ 445228</b>

Notes: (1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-packed. Perform proper lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377957
Diam. intérieur	69.85 mm
Diam. extérieur	107.95 mm
Épaisseur	44.45 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE