

Roulement à aiguilles GBRI446832-IKO - GBRI446832-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/gbri446832-iko>



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F_w
69.850 (2 3/8)	GBRI 446832	1 840	69.850 2 3/8	107.950 4 1/8	50.800 2	51.050	82.550 3 1/8
Standard mounting dimensions mm		Dynamic load rating C N	Basic load rating C ₀ N	Allowable rotational speed (*) rpm	Assembled inner ring		
d_a Min.	d_a Max.				$r_{as\ max}$ (*)		
77	79	99.9	1.5	214 000	452 000	1 800	LRBZ 445232

Notes: (*) Maximum permissible corner radius of the housing.
 (*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
 Remarks: 1. The outer ring has an oil groove and an oil hole.
 2. No grease is pre-applied. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377964
Diam. intérieur	69.85 mm
Diam. extérieur	107.95 mm
Épaisseur	50.8 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE