


Roulement à aiguilles GBRI527632-IKO - GBRI527632-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/gbri527632-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
82.550 (3 1/4)	GBRI 527632	2 110	82.550 (3 1/4)	120.650 (4 3/4)	50.800 (2)	51.050	95.250 (3 3/4)
Standard mounting dimensions mm		Sub-dynamic load rating C ₁₀ N	Basic load rating C ₀ N	Allowable rotational speed (1) rpm	Assembled inner ring		
d _a Min.	d _a Max.				r _{as} mm	r _{is} mm	
91	93	112.6	1.5	228 000	522 000	1 600	LRBZ 526032

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377988
Diam. intérieur	82.55 mm
Diam. intérieur	3 1/4" inch
Diam. extérieur	120.65 mm
Diam. extérieur	4 3/4" inch
Epaisseur	50.8 mm
Epaisseur	2" inch
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE