

Roulement à aiguilles RNA49-32-U-IKO - RNA49-32-U-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/rna49-32-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_a (1)
40	—	RNA 49/32U	—	—	94.5	40	52	20	0.6

Standard rounding dimension D_s Max. mm	Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed(2)
48	29 400	44 200	5 000 rpm

Notes (1)
(1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952379142
Diam. intérieur	40 mm
Diam. extérieur	52 mm
Épaisseur	20 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE