


## Roulement à aiguilles RNA49-52-U-IKO - RNA49-52-U-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/rna49-52-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$F_w$	$D$	$C$	$r_a$ (1)
<b>60</b>	—	<b>RNA 49/52U</b>	—	—	200	60	75	22	0.6
Standard rounding dimension $D_s$ Max. mm	N	N	N	N					
Basic dynamic load rating $C$	42 100	73 600	73 600	3 000					
Basic static load rating $C_0$									
Allowable rotational speed (2)									

Notes: (1) Minimum allowable value of chamfer dimension  $r$ . Allowable rotational speed applies to grease lubrication. The outer ring has an oil groove and an oil hole.  
Remarks: 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952379395
Diam. intérieur	60 mm
Diam. extérieur	75 mm
Épaisseur	22 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE